



4700 Broadmoor SE, Suite 200  
Kentwood, MI 49512

Telephone: 616-656-7401  
Facsimile: 616-656-2022  
www.intertek-etlsemko.com

CF GROUP  
Date: March 16, 2011  
P.O. No.: 810838

Report No.: 100354266GRR-001  
Page 1 of 13

**Test Report For:**  
**CF GROUP**  
**ANSI/BIFMA X5.5-2008**  
**FOR DESK/TABLE PRODUCTS**  
**Plico Table**

  
**Lynwood Pearson**  
**Project Manager**

  
**Bryan Stratton**  
**Reviewer**

*This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.*



CF GROUP  
Date: March 16, 2011  
P.O. No.: 810838

Report No.: 100354266GRR-001  
Page 2 of 13

Attention: David Burgner  
CF Group  
150 Shelby Williams Drive  
Morristown, TN 37813  
Phone (800) 732-8464 ext. 361  
Fax: (423) 318-7313  
Email dburgner@commercialfurnituregroup.com

**DATE RECEIVED:** 3/4/2011  
**DATES TESTED:** 3/8/2011-3/11/2011

**DESCRIPTION OF SAMPLES:**

Part Description: Plico  
Material Submitted: Production  
Condition of Test Sample: New

**WORK REQUESTED/APPLICABLE DOCUMENTS:**

To test the submitted samples per ANSI/BIFMA X5.5-2008 Desk Product Test Standard for the following test program:

<u>Test Number</u>	<u>Test Description</u>
4.3	Stability Under Vertical Load Test
5	Unit Strength Test
6	Top Load Cycle Test
7	Desk/Table Unit Drop Test
8	Leg Strength Test

**CONCLUSION:**

The submitted sample meets the acceptance criteria.

**TEST EQUIPMENT:**

Asset	Description	Cal Date	Cal Due
138012	SCALE / 0-1,000 #	12/04/2009	12/04/2011
138022	DIGITAL/ 0-1,000 READOUT/ LOAD 1,000 LBS.	03/17/2009	03/30/2011
138022.2	LOAD CELL / 0-1,000 # 1-3000 LBS.	03/17/2009	03/30/2011
138112	GRADUATED RULE 36"	08/27/2008	08/27/2013
138185	STOPWATCH	02/18/2008	VBU
138914	FORCE GAUGE	03/06/2009	03/30/2011

**4.3 STABILITY UNDER VERTICAL LOAD TEST:**

Date Tested: 3/9/2011  
Condition of Test Sample: New

Test Procedure:

Test Method: ANSI/BIFMA X5.5-2008; Test No. 4

The unit shall be leveled. Placement of the load shall be on a 12" diameter disk 1" from the edge at the least stable position.

Top Load: 125 lbs.  
Number of Samples Tested: One (1)

Acceptance Criteria:

The unit shall not tip over.

Results:

The sample meets the acceptance criteria. Refer to the following page for photograph.



**Stability Under Vertical Load Test**

**5. UNIT STRENGTH TEST:**

Date Tested: 3/9/2011  
Condition of Test Sample: New

Test Procedure:

Test Method: ANSI/BIFMA X5.5-2008, Test No. 5

Surfaced to be Tested (Class):	work surface
Surface Size:	29-1/2 x 59
<u>Concentrated Load (lbs)</u>	
Functional:	200 lbs.
Proof:	300 lbs.
<u>Distributed Load (lbs)</u>	
Functional:	265 lbs.
Proof:	407 lbs.

Number of Samples Tested: One (1)

Acceptance Criteria:

Functional Load: There shall be no loss of serviceability.

Proof Load: There shall be no major change in the structural integrity.

Results:

The sample meets the acceptance level criteria. Refer to the following page for photograph.



**Concentrated Functional Load**



**Concentrated Proof Load**



**Distributed Functional Load**



**Distributed Proof Load**

**6 – TOP LOAD EASE TEST:**

Date Tested: 3/8/2011-3/9/2011  
Condition of Test Sample: New

Test Procedure:

Test Method: ANSI/BIFMA X5.5-2008, Test No. 6

Number of Cycles: 10,000  
Load: 200 lbs.  
Cycles Per Minute: 14 ± 6  
Load Drawers with: 0.017 lb/cu. In.  
Load Area: 16" Diameter  
Number of Samples Tested: One (1)

Acceptance Criteria:

No loss of serviceability. A pull force to overcome anti-rebound or interlock and to fully extend the drawer shall not exceed 11.2 lbs.

Results:

Number of Cycles	Description of Results
10,000	Pass

The sample meets the acceptance level criteria. Refer to the following page for photograph.



**Top Load Ease Test**

**7 – DESK/TABLE UNIT DROP TEST:**

Date Tested: 3/11/2011  
Condition of Test Sample: New

Test Procedure:

Test Method: ANSI/BIFMA X5.5-2008; Test No. 7

NOTE: Test applies to freestanding Category 1 Desk or Tables that are less than 72" in length. Test does not apply to units with casters.

Set all adjustable features at midpoint.

Weight of Unit: 57 lbs.  
Height of Drop: 7.1"

Number of Samples Tested: One (1)

Acceptance Criteria:

There shall be no loss of serviceability.

Results:

The sample meets the acceptance criteria. Refer to the following page for photograph.



**Desk/Table Unit Drop Test**

**8 – LEG STRENGTH TEST:**

Date Tested: 3/11/2011  
Condition of Test Sample: New

Test Procedure:

Test Method: ANSI/BIFMA X5.5-2008; Test No. 8

NOTE: Based on the Desk or Table Category.  
Calculate Functional and Proof Loads.

Unit Weight: 57 lbs.

Functional Load:

Inward Static Load to Leg: 78 lbf.  
Outward Static Load to Leg: 39 lbf.

Proof Load:

Inward Static Load to Leg: 117 lbf.  
Outward Static Load to Leg: 58 lbf.

Number of Samples Tested: One (1)

Acceptance Criteria:

Functional Load: No loss of serviceability.

Proof Load: No major changes in the structural integrity.

Results:

The sample meets the acceptance criteria. Refer to the following page for photographs.



**Leg Strength Test Inward**



**Leg Strength Test Outward**